

## CN-7-...

Non contact voltage detector 11 kV to 66 kV

### Application:

- Non-contact voltage detector, voltage range from 3 kV to 765 kV.
- Approximate detection distances (varying with the environment): 150 mm mini (11 kV) to 700 mm mini (66 kV)
- Ultra-compact, switchless series to ensure permanent operator safety (indoor and outdoor use).

### Features:

- Nominal network range: 3 kV - 765 kV (8 ranges model proposed).
- 360° light indication.
- Self test function.
- Precise and stable operating threshold.
- Reduced sensitivity to induced voltages and to interference fields.
- Temperature conditions: class N (-25°C to +55°C).
- Power supply: 1 standard 9 V battery 6LR61.
- Network frequencies: 50 to 60 Hz.
- High environmental resistance (impact, vibrations, moisture) due to robust thermoplastic housing.

### Composition:

- Packaging: supplied in a carrying bag.

### Optional accessories:

- Recommended insulating sticks: [CE-4-21](#), [CE-9](#), [CE-5](#)



| Ref            | Weight | Length    | Voltages for use |
|----------------|--------|-----------|------------------|
|                |        | Frequency | Voltage range    |
| CN-7-011-066-K | 300    | 50-60 Hz  | 11 kV - 66 kV    |